







Ultraviolet Water Purifier Comparison Chart

(S) - Standard (O) - Optional

Features

	 1.5 to 3 gallons per minute	 1 to 9 gallons per minute	 2 to 20 gallons per minute	 2 to 20 gallons per minute	 40 to 416 gallons per minute	 90 to 450 gallons per minute
Stainless Steel Construction	S	S	S	S	S	S
Ultraviolet Germicidal Lamp with 10,000 Hours Rated Effective Life	S	S	S	S	S	S
Quick Lamp Change with the Easy Off™ Retainer Cap	S	S	S	S	S	S
Fused Quartz Sleeve	S	S	S	S	S	S
Lamp Out Indicator Light(s)	S	S	-	-	-	S
Sight Port to View Lamp Operation	-	-	S	S	S	S
Drain Fitting	-	-	S	S	S	S
Patented Dual Action Wiper Mechanism - <i>Manual</i>	-	-	-	S	S	O
Patented Dual Action Wiper Mechanism - <i>Automatic</i>	-	-	-	-	-	O
Flanged Heads that can be removed or rotated	-	-	-	-	S	S
Sediment and Carbon filter	S	-	-	-	-	-
Mounting Kit	S	O	O	O	O*	-
Guardian™ Ultraviolet Monitor	-	-	O	O	O	S
Sentry™ Safety Sensor	O	O	O	O	O	-
Audio Alarm	O	O	O	O	O	O
Solenoid Valves	-	O	O	O	O	-
Flow Control Valves	-	O	O	O	O	-
Elapsed Time Indicator	O	O	O	O	O	S
Time Delay Mechanism	-	O	O	O	O	-
Residential use	X	X	X	X	X	-
Commercial Use	-	-	X	X	X	X

* Model S10,000C & larger come equipped with mounting rack.